

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)
Issue date: 05-13-2025 Version: 1.0

SECTION 1 Identification**1.1. GHS Product identifier**

Product form : Mixture
Product name : Upper Cylinder Lubricant Fuel Treatment
Type of product : Fuel additives
Part Number : 20013

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Fuel additives

1.4. Supplier's details

Lucas Oil Products, Inc.
3199 Harrison Way NW
Corydon, IN, 47112
USA
T 800-342-2512
sds@lucasoil.com - www.LucasOil.com

1.5. Emergency phone number

Emergency number : For Chemical Emergency Call ChemTel 24hr/day 7days/week
Within USA, Canada, Puerto Rico and US Virgin Islands: 1-800-255-3924
International: 1-813-248-0585
(collect calls accepted)

SECTION 2 Hazard identification**2.1. Classification of the substance or mixture****Classification (GHS CA)**

Not classified

2.2. GHS label elements, including precautionary statements**GHS CA labeling**

No labeling applicable

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3 Composition/information on ingredients**3.1. Substances**

Not applicable

Upper Cylinder Lubricant Fuel Treatment

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Distillates (petroleum), hydrotreated heavy paraffinic	Distillates (petroleum), hydrotreated heavy paraffinic distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	80 - 100*	Asp. Tox. 1, H304

*Chemical name, CAS number and/or exact concentration have been withheld as CBI

*Contains fixed concentration

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.
First-aid measures after skin contact	: Get medical attention if symptoms occur. Wash skin with plenty of water.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. When in doubt or if symptoms are observed, get medical advice. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Rinse mouth out with water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Call a poison center/doctor/physician if you feel unwell.
First-aid measures general	: If you feel unwell, seek medical advice.
Personal protection for first-aid responders.	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: Not expected to present a significant skin hazard under anticipated conditions of normal use.
Symptoms/effects after eye contact	: Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
Symptoms/effects after ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5 Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard. In case of fire and/or explosion do not breathe fumes.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Carbon dioxide. Carbon monoxide.

Upper Cylinder Lubricant Fuel Treatment

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

5.3. Special protective actions for fire-fighters

- Firefighting instructions : Evacuate area. Eliminate all ignition sources if safe to do so. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment. Do not enter fire area without proper protective equipment, including respiratory protection.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.
- Environmental precautions : Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.2. Methods and materials for containment and cleaning up

- For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
- Methods for cleaning up : Take up liquid spill into absorbent material. Move containers from spill area. Take up liquid spill into absorbent material. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Clean contaminated surfaces with an excess of water.
- Other information : Dispose of materials or solid residues at an authorized site.
- For further information refer to section 8: "Exposure controls/personal protection", For further information refer to section 13

SECTION 7 Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Do not breathe vapors. Avoid contact with skin and eyes.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep in a cool, well-ventilated place away from heat.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, Heat sources. Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
- Packaging materials : Store always product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

- Appropriate engineering controls : Handle in accordance with good industrial hygiene and safety procedures. Ensure exposure is below occupational exposure limits (where available). Ensure good ventilation of the work station.
- Environmental exposure controls : Avoid release to the environment.

Upper Cylinder Lubricant Fuel Treatment

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

8.3. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 232.222 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.864
Density	: 7.213 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 95.15 mm ² /s
Explosion limits	: No data available
Particle characteristics	: Particle size : Not Applicable

Upper Cylinder Lubricant Fuel Treatment

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	: No additional information available

SECTION 11 Toxicological information

11.1. Likely routes of exposure

Acute toxicity (oral)	: No data available
Acute toxicity (dermal)	: No data available
Acute toxicity (inhalation)	: No data available

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
--------------------	-----------------------------

Skin corrosion/irritation	: No data available
Serious eye damage/irritation	: No data available
Respiratory or skin sensitization	: No data available
Germ cell mutagenicity	: No data available
Carcinogenicity	: No data available
Reproductive toxicity	: No data available
STOT-single exposure	: No data available
STOT-repeated exposure	: No data available

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Aspiration hazard	: Not classified.
-------------------	-------------------

Upper Cylinder Lubricant Fuel Treatment

Viscosity, kinematic	95.15 mm ² /s
----------------------	--------------------------

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Viscosity, kinematic	18 mm ² /s
Hydrocarbon	Yes
Aliphatic, alicyclic or aromatic hydrocarbon	Yes

Symptoms/effects after inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: Not expected to present a significant skin hazard under anticipated conditions of normal use.
Symptoms/effects after eye contact	: Not expected to present a significant eye contact hazard under anticipated conditions of normal use.

Upper Cylinder Lubricant Fuel Treatment

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Symptoms/effects after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

SECTION 12 Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : No data available

Hazardous to the aquatic environment, long-term (chronic) : No data available

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

12.2. Persistence and degradability

Upper Cylinder Lubricant Fuel Treatment	
Persistence and degradability	Biodegradability in water: no data available.

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

Upper Cylinder Lubricant Fuel Treatment	
Bioaccumulative potential	No data available concerning bioaccumulation.

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID

12.4. Mobility in soil

Upper Cylinder Lubricant Fuel Treatment	
Ecology - soil	No additional information available.

12.5. Other adverse effects

Ozone : No data available

Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Disposal must be done according to official regulations.

Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

Additional information : Do not re-use empty containers.

Upper Cylinder Lubricant Fuel Treatment

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 14 Transport information

In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
14.1. UN Number			
Not regulated for transport			
14.2. UN Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group, if applicable			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Special precautions for user

TDG

Not regulated

DOT

Not regulated

IMDG

Not regulated

IATA

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78⁹ and the IBC Code¹⁰

Not applicable

SECTION 15 Regulatory information

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

SECTION 16 Other Information

Issue date : 05-13-2025

Upper Cylinder Lubricant Fuel Treatment

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Full text of hazard classes and H-statements:

H304	May be fatal if swallowed and enters airways
------	----------------------------------------------

Safety Data Sheet (SDS), Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.