

# LENTEK™ Acrylic Pro Siliconized Acrylic Sealant

LENTEK™ Acrylic Pro Siliconized Acrylic Sealant is a siliconized acrylic sealant that provides a mildew- and water-resistant seal for indoor and outdoor use. Ideal for windows, doors, kitchens, and baths—delivering strong adhesion and lasting performance professionals can trust.



## FEATURES AND BENEFITS

- Indoor and outdoor
- Mildew and water resistant
- Crack proof
- Paintable
- Low odor
- Easy application
- Adheres to wood, PVC, aluminum, glass, tile, stone, concrete, brick, and plaster

## APPLICATIONS

- Windows and doors
- Tubs and showers
- Baseboards and molding
- Ductwork and vents
- Countertops and sinks
- Trim
- Fixtures
- Tile

## INSTRUCTIONS

- Surface must be clean, dry, and free of contaminants
- Cut nozzle at 45° angle
- Load cartridge into caulk gun
- Fill gap or joint with sealant. If necessary, tool before sealant skins over
- Allow sealant to dry at least 2 hours (longer in cool or humid conditions) before painting
- Wait 12 hours before exposing to water

### Surface Preparation

Glass	Degrease with alcohol
Aluminum, light alloys, and stainless steel	Degrease with alcohol
Other metals	Lightly abrade then degrease as above
Wood	Lightly abrade then remove dust
Plastics	Degrease using an agent recommended by plastics manufacturer
Concrete and other alkaline surfaces	Brush and remove dust

## RESTRICTIONS

Do not use LENTEK™ Acrylic Pro Siliconized Acrylic Sealant for sealing joints permanently exposed to water or in high risk areas subject to rain and frost.

## LENTEK™ Acrylic Pro Siliconized Acrylic Sealant

### SAFETY

- Do not breathe dust, fume, gas, mist, vapors, spray
- Wash hands, forearms, and face thoroughly after handling
- Do not eat, drink, or smoke when using this product
- If exposed or concerned: Call a poison center or doctor
- Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national, and/or international regulations.
- Causes damage to organs if swallowed
- This product can expose you to Ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm
- For more information and advice on the safe handling, storage, and disposal of chemical products, users shall refer to the most recent Safety Data Sheet containing physical, ecological, and toxicological, and other safety related data

### STORAGE AND SHELF LIFE

- 18 months if stored properly between 41°F to 77°F (5°C to 25°C)
- Store product in a cool and dry place

### STANDARDS

Meets or exceeds the requirements of the following specifications:

- SCAQMD rule 1168 for sealants and adhesives
- LEED credit EQc4.1: Low-emitting materials
- ASTM C 834

### PROPERTIES

Color	White or Clear	
Chemical Base	Acrylic Dispersion	
Consistency	Paste	
pH	7-9	
Specific Gravity	1.60 ± 0.03 g/cm <sup>3</sup>	(ASTM D 792)
Tack-Free Time	50 ± 20 min (73.4°F (23°C) and 50% R.H)	(ASTM C 679)
Cure Rate	2 mm/day (73.4°F (23°C) and 50% R.H)	
Shore A Hardness	30-50 Shore A	
Ultimate Elongation	≥ 300%	(ASTM D 412)
Temperature Resistance	14°F to 176°F (-10°C to 80°C)	
Application Temperature	41°F to 104°F (5°C to 40°C)	

### Joint Dimensions

Joint Width	5 mm	10 mm	15 mm	20 mm	25 mm
Joint Depth	3 mm	5 mm	8 mm	10 mm	12 mm
Efficiency/310 ml	20 meters	6 meters	2.5 meters	1.50 meters	1 meter

### PACKAGING

PART N°	PRODUCT	COLOR	SIZE	CASE / PALLET
7400003	LENTEK™ Acrylic Pro	Clear	10.5 FL OZ	12 / 1,296
7400004	LENTEK™ Acrylic Pro	White	10.5 FL OZ	12 / 1,296

### DISCLAIMER

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.