

# Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024  
Issue date: 3/31/2025 Revision date: 3/31/2025 Version: 1.0



## LENTEK™ Plumbers Pro Siliconized Acrylic Sealant, Clear

### SECTION 1: Identification

#### 1.1. Product identifier

Product form : Mixture  
Product name : LENTEK™ Plumbers Pro Siliconized Acrylic Sealant

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Expanding joints between prefabricated construction elements  
Assembling wood, PVC, iron, and aluminum joinery  
Sealing joints in stone, wood, concrete, plaster, and brickwork  
Sealing window and door frames to masonry

#### 1.4. Supplier

Lentus LLC  
400 Ring Road  
Elizabethtown, KY 42701  
USA  
T 270-765-2212

#### 1.5. Emergency phone number

Emergency number : Chemtrec: 800-424-9300 (US) or +1-703-527-3887 (International)

### SECTION 2: Hazard Identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Not classified

#### 2.2. Label elements

##### GHS US labeling

No labeling applicable

#### 2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

#### 2.4. Hazards not otherwise classified

No additional information available

#### 2.5. Unknown acute toxicity

No additional information available

## LENTEK™ Plumbers Pro Siliconized Acrylic Sealant, Clear

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

This mixture does not contain any substances to be mentioned according to the criteria for section 3.2 of HCS

### SECTION 4: First aid measures

#### 4.1. Description of necessary first-aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

#### 4.2. Most important symptoms/effects, acute and delayed

- Symptoms/effects after inhalation : Not expected to be a primary route of exposure. May cause irritation to the respiratory tract.
- Symptoms/effects after skin contact : Not expected to be a primary route of exposure. May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
- Symptoms/effects after eye contact : Not expected to be a primary route of exposure. May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/effects after ingestion : Not expected to be a primary route of exposure. May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

#### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

- Other medical advice or treatment : Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>), Dry chemical powder, Water spray. Foam.
- Unsuitable extinguishing media : Do not use water jet.

## LENTEK™ Plumbers Pro Siliconized Acrylic Sealant, Clear

### 5.2. Specific hazards arising from the chemical

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon. Toxic fumes.

### 5.3. Special protective equipment and precautions for fire -fighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

#### For non-emergency personnel

No additional information available

#### For emergency responders

Environmental precautions : Prevent entry to sewers and public waters.

### 6.2. Methods and materials for containment and cleaning up

For containment : Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation. Can be cleaned with water before curing. Cured material can only be removed mechanically.

For further information refer to section 8: "Exposure controls/personal protection"

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not swallow. Handle and open container with care. When using do not eat, drink, or smoke.

Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

Handling temperature : 41°F - 95°F (5°C - 35°C)

### 7.2. Conditions for safe storage, including incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store in a dry, cool, and well-ventilated place. Protect from freezing. Keep out of direct sunlight.

Storage temperature : 41°F - 95°F (5°C - 35°C)

## LENTEK™ Plumbers Pro Siliconized Acrylic Sealant, Clear

Maximum storage period : 18 months

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

No additional information available

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

#### 8.3. Individual protection measures, such as personal protective equipment

##### Hand protection:

Wear suitable gloves. Consult glove manufacturer's product information on material suitability and material thickness.

##### Eye protection:

Safety glasses or goggles are recommended when using product.

##### Skin and body protection:

Wear suitable protective clothing.

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink, or smoke when using this product.

### SECTION 9: Physical and chemical properties

#### 9.1. Basic physical and chemical properties

Physical state : Liquid  
Appearance : Paste  
Color : Clear  
Odor : Characteristics  
Odor threshold : No data available  
pH : No data available  
Melting point : No data available  
Freezing point : No data available  
Boiling point : No data available  
Flash point : No data available  
Flammability (solid, gas) : Not flammable  
Vapor pressure : No data available  
Relative vapor density at 68°F (20°C) : No data available

## LENTEK™ Plumbers Pro Siliconized Acrylic Sealant, Clear

Relative density	:	No data available
Specific gravity	:	1.02 - 1.08 g/cm <sup>3</sup> [Specific gravity density]
Solubility	:	Soluble in water
Partition coefficient n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity, kinematic	:	No data available
Explosion limits	:	No data available
Particle characteristics	:	No data available

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Heat. Incompatible materials.

### 10.5. Incompatible materials

Strong oxidizers. Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Toxic fumes.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	:	Not classified
Acute toxicity (dermal)	:	Not classified
Acute toxicity (inhalation)	:	Not classified
Skin corrosion/irritation	:	Not classified
Serious eye damage/irritation	:	Not classified
Respiratory or skin sensitization	:	Not classified
Germ cell mutagenicity	:	Not classified
Carcinogenicity	:	Not classified
Reproductive toxicity	:	Not classified
STOT-single exposure	:	Not classified
STOT-repeated exposure	:	Not classified

# Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024  
Issue date: 3/31/2025 Revision date: 3/31/2025 Version: 1.0



## LENTEK™ Plumbers Pro Siliconized Acrylic Sealant, Clear

Aspiration hazard : Not classified

LENTEK™ Plumbers Pro Siliconized Acrylic Sealant	
Viscosity, kinematic	No data available

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.  
Symptoms/effects after skin contact : May cause skin irritation. Repeated exposure may cause skin dryness or cracking.  
Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.  
Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.  
Other information : Likely routes of exposure: ingestion, inhalation, skin, and eye.

### SECTION 12: Ecological information

#### 12.1. Ecotoxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Not classified

#### 12.2. Persistence and degradability

LENTEK™ Plumbers Pro Siliconized Acrylic Sealant	
Persistence and degradability	Rapidly degradable

#### 12.3. Bioaccumulative potential

LENTEK™ Plumbers Pro Siliconized Acrylic Sealant	
Bioaccumulative potential	Not established

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Ozone : Not classified  
Fluorinated greenhouse gases : No  
Other information : No other effects known

### SECTION 13: Disposal considerations

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

## LENTEK™ Plumbers Pro Siliconized Acrylic Sealant, Clear

### SECTION 14: Transport information

In accordance with DOT

#### 14.1. UN number

UN-No. (DOT) : Not regulated

#### 14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Not regulated

#### 14.3. Transport hazard class(es)

##### DOT

Transport hazard class(es) (DOT) : Not regulated

#### 14.4. Packing group

Packing group (DOT) : Not regulated

#### 14.5. Environmental hazards

Other information : No supplementary information available.

#### 14.6. Transport in bulk

Not applicable

#### 14.7. Special precautions for user

Not applicable

### SECTION 15: Regulatory information


#### 15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

#### 15.2. International regulations

No additional information available

#### 15.3. State regulations

 **WARNING:** This product can expose you to Ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### SECTION 16: Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

Revision date : 3/31/2025

Issue date : 3/31/2025

Other information : None

Prepared by : Nexreg Compliance Inc.

[www.Nexreg.com](http://www.Nexreg.com)



## LENTEK™ Plumbers Pro Siliconized Acrylic Sealant, Clear

Safety Data Sheet (SDS), USA

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.