

# LENTEK™ Plumbers Pro Siliconized Acrylic Sealant, White

LENTEK™ Plumbers Pro Siliconized Acrylic Sealant is a siliconized acrylic sealant that creates a watertight, flexible seal around tubs, sinks, ducts, and fixtures. Paintable, mildew-resistant, and easy to apply—built for clean, long-lasting results.



## FEATURES AND BENEFITS

- Mildew and water resistant
- Paintable
- Flexible and durable
- Indoor and outdoor
- One-component
- Easy application
- Forms a permanent water-repellent layer after curing
- Does not affect the application surface
- Adheres to wood, PVC, aluminum, glass, tile, stone, concrete, brick, and plaster

## APPLICATIONS

- Tubs and showers
- Countertops and sinks
- Vanities and cabinets
- Fixtures
- Tile
- Windows and doors
- Baseboards and molding
- Ductwork and vents

## INSTRUCTIONS

- Surface must be clean, dry, and free of contaminants
- Remove cap and cut tube for angle and size needed
- Gently squeeze tube to apply
- Smooth bead with tool
- Reseal tube for storage and reuse
- Can be cleaned from all tools and application equipment with water before curing. Cured material can only be removed mechanically
- Paintable when fully dry. Test compatibility with paint before application

## RESTRICTIONS

Do not use LENTEK™ Plumbers Pro Siliconized Acrylic Sealant on oil leaking materials such as bituminous substrates or natural and synthetic rubber.

## LENTEK™ Plumbers Pro Siliconized Acrylic Sealant, White

### SAFETY

- Keep out of reach of children
- Avoid contact with skin and eyes. Use gloves before application
- Keep out of freezing, direct sunlight, and temperatures above 104°F (40°C)
- Apply in well-ventilated areas
- For more information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet containing, physical, ecological, and toxicological and other safety related data

### STORAGE AND SHELF LIFE

- 18 months if stored properly between 41°F to 77°F (5°C to 25°C)
- Store product in a cool and dry place

### STANDARDS

Meets or exceeds the requirements of the following specifications:

- ASTM C 834

### PROPERTIES

Color	White	
Chemical Base	Acrylic	
Specific Gravity	1,64 ± 0,03 g/cm <sup>3</sup>	(SEL DM-04)
Tack-Free Time	15-60 min	(25°C and 50% R.H)
Paint Over Time	2 hrs	
Water Exposure Time	12-16 hrs	
Cure Rate	2 mm/24 hrs	(25°C and 50% R.H)
Tensile Strength at Break	≥ 0,1 Mpa	(SEL DM-05)
Elongation at Break	≥ 100%	(SEL DM-05)
Modulus 100% Elongation	> 0,2 Mpa	(SEL DM-05)
Application Temperature	41°F to 95°F (5°C to 35°C)	
Temperature Resistance	14°F to 176°F (-10°C to 80°C)	

### Joint Dimensions

Min. Width	5 mm	
Max. Width	15 mm	
Min. Depth	5 mm	

Recommended joint dimensions: Width = 2 × depth

Use backing rod in wide joints to control depth and prevent three-sided adhesion

### PACKAGING

PART N°	PRODUCT	COLOR	SIZE	CASE / PALLET
7400002	LENTEK™ Plumbers Pro	White	5.5 FL OZ	24 / 1,248

### DISCLAIMER

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.