SAFETY DATA SHEET

DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC

Product name: MOLYKOTE® G-4700 Extreme Pressure Synthetic Grease

Issue Date: 10/16/2024

Print Date: 10/23/2024

DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: MOLYKOTE® G-4700 Extreme Pressure Synthetic Grease

Recommended use of the chemical and restrictions on use
Identified uses: Lubricants and lubricant additives

COMPANY IDENTIFICATION
DDP SPECIALTY ELECTRONIC MATERIALS
US 9, LLC
974 Centre Road
Wilmington DE 19805
UNITED STATES

Customer Information Number: 833-338-7668
SDSQuestion-NA@dupont.com

EMERGENCY TELEPHONE NUMBER
24-Hour Emergency Contact: 1-800-424-9300
Local Emergency Contact: 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification
GHS classification in accordance with 29 CFR 1910.1200
Eye irritation - Category 2A
Skin sensitisation - Category 1
Reproductive toxicity - Category 1B

Label elements
Hazard pictograms

Signal word: **DANGER!**

Hazards
May cause an allergic skin reaction.
Causes serious eye irritation.
May damage fertility or the unborn child.

Precautionary statements

Prevention
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response
IF ON SKIN: Wash with plenty of soap and water.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/ attention.
If skin irritation or rash occurs: Get medical advice/ attention.
If eye irritation persists: Get medical advice/ attention.
Wash contaminated clothing before reuse.

Storage
Store locked up.

Disposal
Dispose of contents/ container to an approved waste disposal plant.

Other hazards
No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Organic grease
This product is a mixture.

Component	CASRN	Concentration
Molybdenum disulfide	1317-33-5	>= 1.0 - <= 1.5 %
Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	68457-79-4	>= 1.0 - <= 1.4 %
Boric acid, potassium salt	12712-38-8	>= 0.41 - <= 0.51 %
Distillates, petroleum, solvent-refined heavy	64741-88-4	>= 0.38 - <= 0.46 %

paraffinic		
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	>= 0.38 - <= 0.46 %
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1	>= 0.28 - <= 0.42 %
Naphthenic acids	1338-24-5	>= 0.24 - <= 0.36 %

4. FIRST AID MEASURES

Description of first aid measures
Inhalation: Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Skin contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. Suitable emergency safety shower facility should be available in work area. Consult a physician if irritation develops.

Eye contact: Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist. Suitable emergency eye wash facility should be available in work area.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

Most important symptoms and effects, both acute and delayed:
Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed
Notes to physician: Maintain adequate ventilation and oxygenation of the patient. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical

Unsuitable extinguishing media: None known.

Special hazards arising from the substance or mixture

Hazardous combustion products: Carbon oxides Sulphur oxides Metal oxides Oxides of phosphorus

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to health.

Advice for firefighters
Fire Fighting Procedures: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions: Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
See sections: 7, 8, 11, 12 and 13.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not get on skin or clothing. Do not swallow. Do not get in eyes. Keep container tightly closed. Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice.
Use with local exhaust ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Advice on general occupational hygiene
Use good personal hygiene. Do not consume or store food in the work area. Wash hands before smoking or eating. Ensure that eye flushing systems and safety showers are located close to the working place.

Conditions for safe storage: Keep in properly labelled containers. Store locked up. Keep tightly closed. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents. Organic peroxides. Explosives.
Unsuitable materials for containers**:** None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters
If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
Molybdenum disulfide	OSHA Z-1	TWA total dust	15 mg/m3 , Molybdenum
	ACGIH	TWA Inhalable particulate matter	10 mg/m3 , Molybdenum
	ACGIH	TWA Respirable particulate matter	3 mg/m3 , Molybdenum
	CAL PEL	PEL Total dust	10 mg/m3 , Molybdenum
	CAL PEL	PEL respirable dust fraction	3 mg/m3 , Molybdenum
	Further information: (n): The concentration and percentage of the particulate used for this limit are determined from the fraction passing a size selector with the following characteristics: Aerodynamic Diameter in Micrometers (unit density sphere)..... Percent Passing Selector 0 ..... 100 1 ..... 97 2 ..... 91 3 ..... 74 4 ..... 50 5 ..... 30 6 ..... 17 7 ..... 9 8 ..... 5 10 1		
Distillates, petroleum, solvent-refined heavy paraffinic	ACGIH	TWA Inhalable particulate matter	5 mg/m3
	Further information: A4: Not classifiable as a human carcinogen		
	CAL PEL	PEL particulate	5 mg/m3
	Further information: (l): As sampled by method that does not collect vapor.		
	NIOSH REL	TWA Mist	5 mg/m3
	NIOSH REL	ST Mist	10 mg/m3
Distillates (petroleum), solvent-refined light paraffinic	ACGIH	TWA Inhalable particulate matter	5 mg/m3
	Further information: A4: Not classifiable as a human carcinogen		
	CAL PEL	PEL particulate	5 mg/m3
	Further information: (l): As sampled by method that does not collect vapor.		
	NIOSH REL	TWA Mist	5 mg/m3
	NIOSH REL	ST Mist	10 mg/m3

Exposure controls
Engineering measures: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Hygiene measures: Use good personal hygiene. Do not consume or store food in the work area. Wash hands before smoking or eating. Ensure that eye flushing systems and safety showers are located close to the working place.

Individual protection measures
Eye/face protection: Use chemical goggles.
Skin protection
Hand protection: Use gloves chemically resistant to this material. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.
Other protection: Use chemical protective clothing resistant to this material, when there is any possibility of skin contact.
Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	
Physical state	Grease
Color	dark grey
Odor	slight
Odor Threshold	No data available
pH	Not applicable
Melting point/ range	No data available
Freezing point	No data available
Boiling point (760 mmHg)	Not applicable
Flash point	**closed cup** >230 °C (446 °F)
Evaporation Rate (Butyl Acetate = 1)	Not applicable
Flammability (solid, gas)	Not classified as a flammability hazard
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapor Pressure	Not applicable
Relative Vapor Density (air = 1)	No data available
Relative Density (water = 1)	0.87
Water solubility	No data available
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available

Dynamic Viscosity	Not applicable
Kinematic Viscosity	Not applicable
Explosive properties	Not explosive

Oxidizing properties	The substance or mixture is not classified as oxidizing.
Molecular weight	No data available
Particle size	No data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents.

Conditions to avoid: None known.

Incompatible materials: Oxidizing agents

Hazardous decomposition products: Ethane. Ethylene. 1-Butene. Hexene. Propylene.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity
Product test data not available. Refer to component data.

Acute dermal toxicity
Product test data not available. Refer to component data.

Acute inhalation toxicity
Product test data not available. Refer to component data.

Skin corrosion/irritation
Product test data not available. Refer to component data.

Serious eye damage/eye irritation
Product test data not available. Refer to component data.

Sensitization
Product test data not available. Refer to component data.

Specific Target Organ Systemic Toxicity (Single Exposure)
Product test data not available. Refer to component data.

Specific Target Organ Systemic Toxicity (Repeated Exposure)
Product test data not available. Refer to component data.

Carcinogenicity
Product test data not available. Refer to component data.

Teratogenicity
Product test data not available. Refer to component data.

Reproductive toxicity
Product test data not available. Refer to component data.

Mutagenicity
Product test data not available. Refer to component data.

Aspiration Hazard
Product test data not available. Refer to component data.

COMPONENTS INFLUENCING TOXICOLOGY:

Molybdenum disulfide

Acute oral toxicity
LD50, Rat, > 2,000 mg/kg No deaths occurred at this concentration.

Acute dermal toxicity
LD50, Rat, male and female, > 2,000 mg/kg No deaths occurred at this concentration.

Acute inhalation toxicity
LC50, Rat, 4 Hour, dust/mist, > 2.82 mg/l No deaths occurred at this concentration.

Skin corrosion/irritation
Brief contact is essentially nonirritating to skin.
Prolonged contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation
May cause slight temporary eye irritation.
Corneal injury is unlikely.

Sensitization
For skin sensitization:
Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)
Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)
No relevant data found.

Carcinogenicity
No relevant data found.

Teratogenicity
No relevant data found.

Reproductive toxicity
No relevant data found.

Mutagenicity
For similar material(s): In vitro genetic toxicity studies were negative.

Aspiration Hazard
Based on physical properties, not likely to be an aspiration hazard.

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts

Acute oral toxicity
LD50, Rat, male, 3,600 mg/kg

Acute dermal toxicity
LD50, Rabbit, male and female, > 20,000 mg/kg

Acute inhalation toxicity
The LC50 has not been determined.

Skin corrosion/irritation
Brief contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation
May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

Sensitization
For skin sensitization:
Based on data from similar materials
Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)
Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)
Observations in animals include:
Gastrointestinal irritation.

Carcinogenicity
No relevant data found.

Teratogenicity
No relevant data found.

Reproductive toxicity
No relevant data found.

Mutagenicity
For similar material(s): In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Aspiration Hazard
Based on physical properties, not likely to be an aspiration hazard.

Boric acid, potassium salt

Acute oral toxicity
Single dose oral LD50 has not been determined.

Based on data from similar materials LD50, Rat, > 2,600 mg/kg OECD Test Guideline 401

Acute dermal toxicity
The dermal LD50 has not been determined.

Based on data from similar materials LD50, Rabbit, > 2,000 mg/kg No deaths occurred at this concentration.

Acute inhalation toxicity
The LC50 has not been determined.

Based on data from similar materials LC50, Rat, 4 Hour, dust/mist, > 2.12 mg/l OECD Test Guideline 403

Skin corrosion/irritation
Brief contact is essentially nonirritating to skin.
May cause skin irritation due to mechanical abrasion.

Serious eye damage/eye irritation
Solid or dust may cause irritation or corneal injury due to mechanical action.

Sensitization
For similar material(s):
Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)
Available data are inadequate to determine single exposure specific target organ toxicity.

Specific Target Organ Systemic Toxicity (Repeated Exposure)
Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Carcinogenicity
For similar material(s): Did not cause cancer in laboratory animals.

Teratogenicity
In laboratory animals, boron compounds have caused birth defects only at doses toxic to the mother and have been toxic to the fetus at doses nontoxic to the mother.

Reproductive toxicity
In animal studies, boron compounds have been shown to interfere with fertility in males, and to a lesser degree in females.

Mutagenicity
For similar material(s): In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Aspiration Hazard
Based on physical properties, not likely to be an aspiration hazard.

Distillates, petroleum, solvent-refined heavy paraffinic

Acute oral toxicity
LD50, Rat, > 5,000 mg/kg Estimated.

Acute dermal toxicity
LD50, Rabbit, > 2,000 mg/kg No deaths occurred at this concentration.

Acute inhalation toxicity
The LC50 has not been determined.

Skin corrosion/irritation
Prolonged contact may cause moderate skin irritation with local redness.
Repeated contact may cause moderate skin irritation with local redness.

Serious eye damage/eye irritation
May cause slight temporary eye irritation.
Corneal injury is unlikely.

Sensitization
For this family of materials, sensitization studies done in guinea pigs have been negative.

For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)
Available data are inadequate to determine single exposure specific target organ toxicity.

Specific Target Organ Systemic Toxicity (Repeated Exposure)
No relevant data found.

Carcinogenicity
For similar material(s): Did not cause cancer in animal skin painting studies.

Teratogenicity
No relevant data found.

Reproductive toxicity
No relevant data found.

Mutagenicity
For similar material(s): In vitro genetic toxicity studies were predominantly negative. Animal genetic toxicity studies were negative in some cases and positive in other cases.

Aspiration Hazard
May be fatal if swallowed and enters airways.

Distillates (petroleum), solvent-refined light paraffinic

Acute oral toxicity
Typical for this family of materials. LD50, Rat, > 5,000 mg/kg

Acute dermal toxicity
Typical for this family of materials. LD50, Rabbit, > 5,000 mg/kg

Acute inhalation toxicity
LC50, Rat, male and female, 4 Hour, dust/mist, > 5.53 mg/l

Skin corrosion/irritation
Brief contact may cause slight skin irritation with local redness.
Prolonged contact may cause moderate skin irritation with local redness.

Serious eye damage/eye irritation
May cause slight eye irritation.
Corneal injury is unlikely.

Sensitization
For this family of materials, sensitization studies done in guinea pigs have been negative.

For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)
Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)
For this family of materials:
In animals, effects have been reported on the following organs:
Liver

Carcinogenicity
No relevant information found.

Teratogenicity
Typical for this family of materials. Has been toxic to the fetus in laboratory animals at doses toxic to the mother.

Reproductive toxicity
Typical for this family of materials. Limited data in laboratory animals suggest that the material does not affect reproduction.

Mutagenicity
Typical for this family of materials. In vitro genetic toxicity studies were predominantly negative. For this family of materials: Animal genetic toxicity studies were negative.

Aspiration Hazard
May be fatal if swallowed and enters airways.

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene

Acute oral toxicity
LD50, Rat, > 5,000 mg/kg OECD Test Guideline 401

Acute dermal toxicity
LD50, Rat, > 2,000 mg/kg OECD Test Guideline 402

Acute inhalation toxicity
The LC50 has not been determined.

Skin corrosion/irritation
Brief contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation
May cause slight temporary eye irritation.

Sensitization
Did not cause allergic skin reactions when tested in guinea pigs.

Specific Target Organ Systemic Toxicity (Single Exposure)
The substance or mixture is not classified as specific target organ toxicant, single exposure.

Specific Target Organ Systemic Toxicity (Repeated Exposure)
Based on available data, repeated exposures are not anticipated to cause additional significant adverse effects.

Teratogenicity
Has been toxic to the fetus in laboratory animals at doses toxic to the mother.

Reproductive toxicity
In animal studies, has been shown to interfere with reproduction.

Mutagenicity
In vitro genetic toxicity studies were negative. Information given is based on data obtained from similar substances.

Aspiration Hazard
No aspiration toxicity classification

Naphthenic acids

Acute oral toxicity
LD50, Rat, 5,880 mg/kg

Acute dermal toxicity

LD50, Rabbit, > 3,160 mg/kg OECD Test Guideline 402

Acute inhalation toxicity
The LC50 has not been determined.

Skin corrosion/irritation
Brief contact may cause moderate skin irritation with local redness.

Sensitization
Has caused allergic skin reactions when tested in guinea pigs.

Specific Target Organ Systemic Toxicity (Single Exposure)
The substance or mixture is not classified as specific target organ toxicant, single exposure.

Specific Target Organ Systemic Toxicity (Repeated Exposure)
Based on available data, repeated exposures are not anticipated to cause additional significant adverse effects.

Teratogenicity
Did not cause birth defects or any other fetal effects in laboratory animals.

Reproductive toxicity
In animal studies, did not interfere with reproduction.

Mutagenicity
Animal genetic toxicity studies were negative. In vitro genetic toxicity studies were predominantly negative. This material was not mutagenic in an Ames bacterial assay. Information given is based on data obtained from similar substances.

Aspiration Hazard
No aspiration toxicity classification

Carcinogenicity

Component	List	Classification
Distillates, petroleum, solvent-refined heavy paraffinic	IARC	Group 1: Carcinogenic to humans
Distillates (petroleum), solvent-refined light paraffinic	IARC	Group 1: Carcinogenic to humans
	US NTP	Known to be human carcinogen

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity

Molybdenum disulfide

Acute toxicity to fish
Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
For similar material(s):

LC50, Fish, 96 Hour, > 100 mg/l

Acute toxicity to aquatic invertebrates
Based on data from similar materials
EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l

Acute toxicity to algae/aquatic plants
Based on data from similar materials
ErC50, algae, 72 Hour, Growth rate, > 100 mg/l

Toxicity to bacteria
EC50, 30 Hour, Respiration rates., > 100 mg/l

Chronic toxicity to fish
Based on data from similar materials
NOEC, Fish, 34 d, > 10 mg/l

Chronic toxicity to aquatic invertebrates
Based on data from similar materials
NOEC, Daphnia magna, 21 d, > 10 mg/l

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts

Acute toxicity to fish
Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).
Based on data from similar materials
LL50, Cyprinodon variegatus (sheepshead minnow), semi-static test, 96 Hour, 4.5 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates
Based on data from similar materials
EL50, Daphnia magna (Water flea), static test, 48 Hour, 23 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants
Based on data from similar materials
EL50, Desmodesmus subspicatus (green algae), 72 Hour, 24 mg/l, OECD Test Guideline 201

Toxicity to bacteria
Based on data from similar materials
EC50, 3 Hour, > 1,000 mg/l, OECD Test Guideline 209

Chronic toxicity to aquatic invertebrates
Based on data from similar materials
NOEC, Daphnia magna (Water flea), 21 d, 0.4 mg/l

Boric acid, potassium salt

Acute toxicity to fish
Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
Based on data from similar materials
LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, > 1,000 mg/l

Acute toxicity to aquatic invertebrates

For similar material(s):
EC50, Daphnia magna (Water flea), 48 Hour, > 1,000 mg/l

Acute toxicity to algae/aquatic plants
Based on data from similar materials
ErC50, Pseudokirchneriella subcapitata (green algae), 96 Hour, > 120 mg/l
Based on data from similar materials
NOEC, Pseudokirchneriella subcapitata (green algae), 96 Hour, 120 mg/l

Toxicity to bacteria
Based on data from similar materials
NOEC, 3 Hour, 20 mg/l

Chronic toxicity to fish
Based on data from similar materials
NOEC, Pimephales promelas (fathead minnow), 32 d, 11.2 mg/l

Chronic toxicity to aquatic invertebrates
Based on data from similar materials
NOEC, Daphnia magna (Water flea), 14 d, 18 mg/l

Distillates, petroleum, solvent-refined heavy paraffinic

Acute toxicity to fish
Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, > 1,000 mg/l

Acute toxicity to aquatic invertebrates
LC50, Daphnia magna (Water flea), 48 Hour, > 1,000 mg/l

Acute toxicity to algae/aquatic plants
EC50, Pseudokirchneriella subcapitata (green algae), 96 Hour, Biomass, > 1,000 mg/l

Toxicity to bacteria
Based on data from similar materials
NOEC, 10 min, > 1.93 mg/l, DIN 38 412 Part 8

Chronic toxicity to fish
NOEC, Pimephales promelas (fathead minnow), 7 d, survival, > 5,000 mg/l

Chronic toxicity to aquatic invertebrates
NOEC, Daphnia magna (Water flea), 21 d, number of offspring, > 1,000 mg/l

Distillates (petroleum), solvent-refined light paraffinic

Acute toxicity to fish
Typical for this family of materials.
Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
For this family of materials:
LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, > 100 mg/l

Acute toxicity to aquatic invertebrates
For this family of materials:

EC50, Daphnia magna (Water flea), semi-static test, 48 Hour, > 100 mg/l

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene

Acute toxicity to fish
LC50, Danio rerio (zebra fish), 96 Hour, > 100 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates
EC50, Daphnia magna (Water flea), 48 Hour, 51 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants
EC50, Desmodesmus subspicatus (green algae), 72 Hour, > 100 mg/l, OECD Test Guideline 201
NOEC, Desmodesmus subspicatus (green algae), 72 Hour, 10 - 100 mg/l, OECD Test Guideline 201

Toxicity to bacteria
IC50, activated sludge, 3 Hour, > 100 mg/l

Chronic toxicity to fish
Information given is based on tests on the mixture itself.
NOEC, Danio rerio (zebra fish), 34 d, 10 mg/l

Naphthenic acids

Acute toxicity to fish
LC50, Pimephales promelas (fathead minnow), 96 Hour, 5.62 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates
LC50, Daphnia magna (Water flea), 48 Hour, 20 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants
EC50, Raphidocelis subcapitata (freshwater green alga), 96 Hour, 29.9 mg/l, OECD Test Guideline 201
NOEC, Raphidocelis subcapitata (freshwater green alga), 96 Hour, 7.41 mg/l, OECD Test Guideline 201

Chronic toxicity to fish
NOEC, Pimephales promelas (fathead minnow), 7 d, 0.4 mg/l

Chronic toxicity to aquatic invertebrates
NOEC, Daphnia magna (Water flea), 21 d, 4.1 mg/l

Persistence and degradability

Molybdenum disulfide
Biodegradability: Biodegradability is not applicable to inorganic substances.

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts
Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.
Based on data from similar materials 10-day Window: Fail
Biodegradation: 1.5 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Boric acid, potassium salt

Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.
Based on data from similar materials 10-day Window: Fail
Biodegradation: 13 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Distillates, petroleum, solvent-refined heavy paraffinic

Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability. Material is inherently biodegradable (reaches > 20% biodegradation in OECD test(s) for inherent biodegradability).
10-day Window: Fail
Biodegradation: 6 %
Exposure time: 28 d
Method: OECD Test Guideline 301B or Equivalent

Distillates (petroleum), solvent-refined light paraffinic

Biodegradability: For this family of materials: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.
10-day Window: Fail
Biodegradation: 1.5 - 29 %
Exposure time: 28 d
Method: OECD Test Guideline 301B or Equivalent

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene

Biodegradability: Material is not readily biodegradable according to OECD/EEC guidelines.

Biodegradation: 0 - 1 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Naphthenic acids

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

Biodegradation: 60 %
Exposure time: 22 d
Method: OECD Test Guideline 310

Bioaccumulative potential

Molybdenum disulfide

Bioaccumulation: Partitioning from water to n-octanol is not applicable.

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts

Bioaccumulation: For similar material(s): Bioconcentration potential is low (BCF < 100 or Log Pow < 3).
Partition coefficient: n-octanol/water(log Pow): 0.69 OECD Test Guideline 107

Boric acid, potassium salt

Bioaccumulation: Based on data from similar materials
Bioconcentration factor (BCF): 8 Lepomis macrochirus (Bluegill sunfish)

Distillates, petroleum, solvent-refined heavy paraffinic
Bioaccumulation: Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and 7).
Partition coefficient: n-octanol/water(log Pow): 3.9 - 6 Estimated.

Distillates (petroleum), solvent-refined light paraffinic
Bioaccumulation: For this family of materials: Bioconcentration potential is low (BCF less than 100 or log Pow greater than 7).

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene
Bioaccumulation: Bioconcentration potential is low (BCF less than 100 or log Pow greater than 7).
Partition coefficient: n-octanol/water(log Pow): >= 5 at 25 °C Estimated.

Naphthenic acids
Bioaccumulation: Bioaccumulation is unlikely. No specific, relevant data available for assessment.
Partition coefficient: n-octanol/water(log Pow): 2.05 - 13.25

Mobility in soil

Molybdenum disulfide
No relevant data found.

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts
No specific, relevant data available for assessment.

Distillates, petroleum, solvent-refined heavy paraffinic
No relevant data found.

Distillates (petroleum), solvent-refined light paraffinic
No relevant data found.

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene
No data available.

Naphthenic acids
No specific, relevant data available for assessment.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR

MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

14. TRANSPORT INFORMATION

DOT

Proper shipping name	Environmentally hazardous substance, solid, n.o.s.(Naphthenic Acids)
UN number	UN 3077
Class	9
Packing group	III
Reportable Quantity	Naphthenic Acids

Classification for SEA transport (IMO-IMDG):

	Not regulated for transport
Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Serious eye damage or eye irritation
Respiratory or skin sensitisation
Reproductive toxicity

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313
The following components are subject to reporting levels established by SARA Title III, Section 313:

Components	CASRN
Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	68457-79-4

California Prop. 65
This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

United States TSCA Inventory (TSCA)
All components of this product are in compliance with the Active inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System
NFPA

Health	Flammability	Instability
2	1	0

HMIS

Health	Flammability	Physical Hazard
2*	1	0

* = Chronic Effects (See Hazards Identification)

Revision
Identification Number: 4044117 / A776 / Issue Date: 10/16/2024 / Version: 8.0
Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
CAL PEL	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
NIOSH REL	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
PEL	Permissible exposure limit
ST	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
TWA	8-hour time weighted average

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References
This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.
US