



SAFETY DATA SHEET

DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC

Product name: Froth-Pak™ POLYOL HFO 200BF cylinder

Issue Date: 11/17/2024

Print Date: 12/06/2024

DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: Froth-Pak™ POLYOL HFO 200BF cylinder

Recommended use of the chemical and restrictions on use

Identified uses: For industrial use. We recommend that you use this product in a manner consistent with the listed use. If your intended use is not consistent with the stated use, please contact your sales or technical service representative.

COMPANY IDENTIFICATION

DDP SPECIALTY ELECTRONIC MATERIALS
US 9, LLC
974 Centre Road
Wilmington DE 19805
UNITED STATES

Customer Information Number:

833-338-7668

SDSQuestion-NA@dupont.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 1-800-424-9300

Local Emergency Contact: 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

GHS classification in accordance with 29 CFR 1910.1200

Gases under pressure - Liquefied gas

Eye irritation - Category 2A

Skin sensitisation - Category 1

Reproductive toxicity - Category 2

Simple Asphyxiant

Label elements

Hazard pictograms



Signal word: **WARNING!**

Hazards

Contains gas under pressure; may explode if heated.
May cause an allergic skin reaction.
Causes serious eye irritation.
Suspected of damaging fertility or the unborn child.
May displace oxygen and cause rapid suffocation.

Precautionary statements

Prevention

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing mist or vapours.
Wash skin thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

IF ON SKIN: Wash with plenty of soap and water.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/ attention.
If skin irritation or rash occurs: Get medical advice/ attention.
If eye irritation persists: Get medical advice/ attention.
Wash contaminated clothing before reuse.

Storage

Store locked up.
Protect from sunlight. Store in a well-ventilated place.

Disposal

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture.

Component

CASRN

Concentration

| | | |
|---|-------------|--------------------|
| trans-1-Chloro-3,3,3-trifluoropropene | 102687-65-0 | >= 20.0 - < 30.0 % |
| Tris(1-chloro-2-propyl) phosphate | 13674-84-5 | >= 10.0 - < 20.0 % |
| Triethyl phosphate | 78-40-0 | >= 5.0 - < 10.0 % |
| Polyethylene glycol | 25322-68-3 | >= 1.0 - < 5.0 % |
| 2-Ethylhexanoic acid potassium salt | 3164-85-0 | >= 1.0 - < 5.0 % |
| Carbon dioxide | 124-38-9 | >= 1.0 - < 5.0 % |
| Diethylene glycol | 111-46-6 | >= 1.0 - < 5.0 % |
| Dimethylbis((1-oxoneodecyl)oxy)stannane | 68928-76-7 | >= 0.1 - < 1.0 % |

4. FIRST AID MEASURES

Description of first aid measures

General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Skin contact: Remove contaminated clothing immediately. Immediately wash skin with soap and plenty of water. Suitable emergency safety shower facility should be available in work area. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. In the case of skin irritation or allergic reactions see a physician.

Eye contact: In case of contact, immediately flush eye with plenty of water. Suitable emergency eye wash facility should be available in work area.

Ingestion: Do not induce vomiting. Call a physician and/or transport to emergency facility immediately.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Maintain adequate ventilation and oxygenation of the patient. If breathing is difficult, oxygen should be administered by qualified personnel. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Unsuitable extinguishing media: Do not use direct water stream. May spread fire.

Special hazards arising from the substance or mixture

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide. Hydrogen halides.

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation. Blowing agent vaporizes quickly at room temperature. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this (M)SDS.

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Isolate area. Keep unnecessary and unprotected personnel from entering the area. Keep personnel out of confined or poorly ventilated areas. Keep upwind of spill. Spilled material may cause a slipping hazard. Ventilate area of leak or spill. Confined space entry procedures must be followed before entering the area. Refer to section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up: Contain spilled material if possible. Absorb with materials such as: Dirt. Sand. Sawdust. Collect in suitable and properly labeled containers. Wash the spill site with water. See Section 13, Disposal Considerations, for additional information.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with eyes. Avoid breathing vapor. Do not enter confined spaces unless adequately ventilated. Wash thoroughly after handling. Keep container closed. Use with adequate ventilation. This material is hygroscopic in nature. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.

Advice on general occupational hygiene

Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage: Minimize sources of ignition, such as static build-up, heat, spark or flame. Flammable vapors may accumulate in some storage situations. Protect from atmospheric moisture. Store in a dry place. Avoid prolonged exposure to heat and air. Avoid temperatures above 50°C (122°F) See Section 10 for more specific information.

Storage stability

Storage Period: 24 Month

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

| Component | Regulation | Type of listing | Value |
|---|------------|-----------------|-------------------------|
| trans-1-Chloro-3,3,3-trifluoropropene | US WEEL | TWA | 800 ppm |
| Triethyl phosphate | US WEEL | TWA | 7.45 mg/m3 |
| Polyethylene glycol | US WEEL | TWA aerosol | 10 mg/m3 |
| Carbon dioxide | Dow IHG | TWA | 5,000 ppm |
| | Dow IHG | STEL | 30,000 ppm |
| | ACGIH | TWA | 5,000 ppm |
| | ACGIH | STEL | 30,000 ppm |
| | OSHA Z-1 | TWA | 9,000 mg/m3 5,000 ppm |
| | CAL PEL | PEL | 9,000 mg/m3 5,000 ppm |
| | CAL PEL | STEL | 54,000 mg/m3 30,000 ppm |
| | NIOSH REL | TWA | 9,000 mg/m3 5,000 ppm |
| | NIOSH REL | ST | 54,000 mg/m3 30,000 ppm |
| Diethylene glycol | DUPONT AEL | AEL * Vapour | 100 ppm |
| | US WEEL | TWA | 10 mg/m3 |
| Dimethylbis((1-oxoneodecyl)oxy)stannane | OSHA Z-1 | TWA | 0.1 mg/m3 , Tin |

| | | | |
|--|---|------|-----------------|
| | ACGIH | TWA | 0.1 mg/m3 , Tin |
| | Further information: A4: Not classifiable as a human carcinogen; Skin: Danger of cutaneous absorption | | |
| | ACGIH | STEL | 0.2 mg/m3 , Tin |
| | Further information: A4: Not classifiable as a human carcinogen; Skin: Danger of cutaneous absorption | | |
| | CAL PEL | PEL | 0.1 mg/m3 , Tin |
| | Further information: S: Skin | | |
| | CAL PEL | STEL | 0.2 mg/m3 , Tin |
| | Further information: S: Skin | | |

Exposure controls

Engineering measures: Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only in enclosed systems or with local exhaust ventilation. Exhaust systems should be designed to move the air away from the source of vapor/aerosol generation and people working at this point. Lethal concentrations may exist in areas with poor ventilation.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields). Where contact with the liquid is likely, chemical goggles are recommended.

Skin protection

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Styrene/butadiene rubber. Viton. Examples of acceptable glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Polyvinyl chloride ("PVC" or "vinyl").
 NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. When respiratory protection is required, use an approved positive-pressure self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus. In confined or poorly ventilated areas, use an approved self-contained breathing apparatus or positive pressure air line with auxiliary self-contained air supply.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

| | |
|-----------------------|---------------------------|
| Physical state | Liquefied gas |
| Color | yellow |
| Odor | No information available. |
| Odor Threshold | No data available |
| pH | No data available |

| | |
|---|---|
| Melting point/ range | No data available |
| Freezing point | No data available |
| Boiling point (760 mmHg) | No data available |
| Flash point | > 200 °C (> 392 °F) |
| Evaporation Rate (Butyl Acetate = 1) | Not available |
| Flammability (solid, gas) | Not applicable to liquids Not expected to form explosive dust-air mixtures. |
| Lower explosion limit | Not applicable |
| Upper explosion limit | Not applicable |
| Vapor Pressure | No data available |
| Relative Vapor Density (air = 1) | No data available |
| Relative Density (water = 1) | No data available |
| Water solubility | Not applicable |
| Partition coefficient: n-octanol/water | No data available |
| Auto-ignition temperature | No data available |
| Decomposition temperature | No test data available |
| Kinematic Viscosity | No data available |
| Explosive properties | Not applicableNot explosive |
| Oxidizing properties | No data available |
| Molecular weight | No data available |

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: No data available

Chemical stability: Stable under recommended storage conditions. See Storage, Section 7.

Possibility of hazardous reactions: Will not occur by itself.

Conditions to avoid: Product can oxidize at elevated temperatures. Elevated temperatures can cause pressure buildup in closed containers due to the release of blowing agents. Generation of gas during decomposition can cause pressure in closed systems.

Incompatible materials: Avoid contact with oxidizing materials. Avoid contact with: Strong acids. Strong bases. Avoid unintended contact with isocyanates. The reaction of polyols and isocyanates generates heat.

Hazardous decomposition products: Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Carbon dioxide. Alcohols. Ethers. Hydrocarbons. Hydrogen halides. Ketones. Polymer fragments.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity

Product test data not available. Refer to component data.

Acute dermal toxicity

Product test data not available. Refer to component data.

Acute inhalation toxicity

Product test data not available. Refer to component data.

Skin corrosion/irritation

Product test data not available. Refer to component data.

Serious eye damage/eye irritation

Product test data not available. Refer to component data.

Sensitization

Product test data not available. Refer to component data.

Specific Target Organ Systemic Toxicity (Single Exposure)

Product test data not available. Refer to component data.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Product test data not available. Refer to component data.

Carcinogenicity

Product test data not available. Refer to component data.

Teratogenicity

Product test data not available. Refer to component data.

Reproductive toxicity

Product test data not available. Refer to component data.

Mutagenicity

Product test data not available. Refer to component data.

Aspiration Hazard

Product test data not available. Refer to component data.

COMPONENTS INFLUENCING TOXICOLOGY:

trans-1-Chloro-3,3,3-trifluoropropene

Acute oral toxicity

Single dose oral LD50 has not been determined.

Acute dermal toxicity

The dermal LD50 has not been determined.

Acute inhalation toxicity

LC50, Rat, 4 Hour, gas, 120000 ppm

Skin corrosion/irritation

Brief contact is essentially nonirritating to skin.

Serious eye damage/eye irritation

No relevant data found.

Sensitization

Did not cause allergic skin reactions when tested in humans.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Carcinogenicity

No relevant data found.

Teratogenicity

No relevant data found.

Reproductive toxicity

No relevant data found.

Mutagenicity

This material was not mutagenic in an Ames bacterial assay.

Aspiration Hazard

Based on available information, aspiration hazard could not be determined.

Tris(1-chloro-2-propyl) phosphate

Acute oral toxicity

LD50, Rat, 1,101 mg/kg OECD Test Guideline 401

Acute dermal toxicity

LD50, Rabbit, > 2,000 mg/kg OECD Test Guideline 402

Acute inhalation toxicity

An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration. LC50, Rat, 4 Hour, dust/mist, > 5 mg/l

Skin corrosion/irritation

Brief contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation

May cause slight temporary eye irritation.

Sensitization

Did not demonstrate the potential for contact allergy in mice.

Specific Target Organ Systemic Toxicity (Single Exposure)

The substance or mixture is not classified as specific target organ toxicant, single exposure.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Teratogenicity

Did not cause birth defects or any other fetal effects in laboratory animals.

Reproductive toxicity

In animal studies, did not interfere with reproduction.

Mutagenicity

Animal genetic toxicity studies were negative. In vitro genetic toxicity studies were negative.

Aspiration Hazard

No aspiration toxicity classification

Triethyl phosphate

Acute oral toxicity

LD50, Rat, 1,131 mg/kg

Acute dermal toxicity

LD50, Guinea pig, > 21,400 mg/kg

Acute inhalation toxicity

LC50, Rat, 4 Hour, dust/mist, > 2.35 mg/l No deaths occurred at this concentration.

Skin corrosion/irritation

Prolonged contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation

May cause moderate eye irritation.

May cause slight corneal injury.

Sensitization

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Triethyl phosphate is considered to be a weak cholinesterase inhibitor. Excessive exposure may produce organophosphate type cholinesterase inhibition. Signs and symptoms of excessive exposure may be headache, dizziness, incoordination, muscle twitching, tremors, nausea, abdominal cramps, diarrhea, sweating, pinpoint pupils, blurred vision, salivation, tearing, tightness in chest, excessive urination, convulsions.

Carcinogenicity

No relevant data found.

Teratogenicity

No relevant data found.

Reproductive toxicity

In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals.

Mutagenicity

In vitro genetic toxicity studies were predominantly negative. Animal genetic toxicity studies were predominantly negative.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

Polyethylene glycol**Acute oral toxicity**

Typical for this family of materials. LD50, Rat, > 10,000 mg/kg Estimated.

Acute dermal toxicity

Typical for this family of materials. LD50, Rabbit, > 20,000 mg/kg

Acute inhalation toxicity

Typical for this family of materials. LC50, Rat, 6 Hour, dust/mist, > 2.5 mg/l No deaths occurred at this concentration.

Skin corrosion/irritation

Prolonged exposure not likely to cause significant skin irritation. May cause more severe response if skin is abraded (scratched or cut).

Serious eye damage/eye irritation

May cause slight temporary eye irritation. Corneal injury is unlikely.

Sensitization

For this family of materials:
Did not cause allergic skin reactions when tested in humans.
For this family of materials, sensitization studies done in guinea pigs have been negative.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Recent findings of kidney failure and death in burn patients, as well as some studies using animal burn models, suggest that polyethylene glycol may have been a factor.

The use of topical applications containing this material may not be appropriate in severely burned patients.

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Carcinogenicity

Polyethylene glycols did not cause cancer in long-term animal studies.

Teratogenicity

Did not cause birth defects or any other fetal effects in laboratory animals.

Reproductive toxicity

In animal studies, did not interfere with reproduction.

Mutagenicity

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

2-Ethylhexanoic acid potassium salt

Acute oral toxicity

Information given is based on data obtained from similar substances. LC50, Rat, 2,043 mg/kg
OECD Test Guideline 401

Acute dermal toxicity

Information given is based on data obtained from similar substances. LD50, Rabbit, > 2,000
mg/kg OECD Test Guideline 402

Acute inhalation toxicity

An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration. LC0, Rat, 4 Hour, dust/mist, > 0.11 mg/l OECD
Test Guideline 403

Skin corrosion/irritation

Brief contact may cause severe skin irritation with pain and local redness.

Serious eye damage/eye irritation

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

Sensitization

Did not cause allergic skin reactions when tested in guinea pigs.

Information given is based on data obtained from similar substances.

No data available

Specific Target Organ Systemic Toxicity (Single Exposure)

The substance or mixture is not classified as specific target organ toxicant, single exposure.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Information given is based on data obtained from similar substances.

Carcinogenicity

No data available

Teratogenicity

Has caused birth defects in laboratory animals. Information given is based on data obtained from similar substances.

Reproductive toxicity

In animal studies, has been shown to interfere with fertility. Information given is based on data obtained from similar substances.

Mutagenicity

Animal genetic toxicity studies were negative. In vitro genetic toxicity studies were negative. Information given is based on data obtained from similar substances.

Aspiration Hazard

No aspiration toxicity classification

Carbon dioxide

Acute oral toxicity

Single dose oral LD50 has not been determined.

Acute dermal toxicity

The dermal LD50 has not been determined.

Acute inhalation toxicity

LC50, Rat, 4 hrs, gas, 58750 ppm

Skin corrosion/irritation

No hazard from gas.

Skin contact with the solid ("dry ice") may cause frostbite.

Liquid may cause frostbite upon skin contact.

Serious eye damage/eye irritation

No hazard from gas.

Eye contact with the solid ("dry ice") may cause freeze burns.

Liquid may cause frostbite.

Sensitization

No relevant data found.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Available data are inadequate to determine single exposure specific target organ toxicity.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Experiments with humans and animals suggest that continued exposure to 1.5% carbon dioxide may alter physiological processes, such as acid-base and electrolyte balance in the blood, calcium-phosphorus metabolism, and neuroendocrine activity.

Carcinogenicity

Available data are inadequate to evaluate carcinogenicity.

Teratogenicity

Available data are inadequate for evaluation of potential to cause birth defects.

Reproductive toxicity

Available data are inadequate to determine effects on reproduction.

Mutagenicity

No relevant data found.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

Diethylene glycol

Acute oral toxicity

In humans, expected to be moderately toxic if swallowed even though oral toxicity was low when tested in animals. Ingestion of quantities (approximately 65 mL (2 oz.) for diethylene glycol or 100 mL (3 oz.) for ethylene glycol) has caused death in humans. May cause nausea and vomiting. May cause abdominal discomfort or diarrhea. Excessive exposure may cause central nervous system effects, cardiopulmonary effects (metabolic acidosis), and kidney failure. LD50, Rat, male, 19,600 mg/kg

Lethal Dose, Human, adult, 2 Ounces Estimated.

Acute dermal toxicity

LD50, Rabbit, 13,330 mg/kg

Acute inhalation toxicity

LC50, Rat, 4 Hour, dust/mist, > 4.6 mg/l The LC50 value is greater than the Maximum Attainable Concentration. No deaths occurred at this concentration.

Skin corrosion/irritation

Prolonged contact is essentially nonirritating to skin.

Serious eye damage/eye irritation

May cause slight temporary eye irritation.

Corneal injury is unlikely.

Sensitization

Did not cause allergic skin reactions when tested in humans.

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

The substance or mixture is not classified as specific target organ toxicant, single exposure.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on available data, repeated exposures are not anticipated to cause additional significant adverse effects.

Carcinogenicity

Diethylene glycol has been tested for carcinogenicity in animal studies and is not believed to pose a carcinogenic risk to man.

Teratogenicity

Diethylene glycol has caused toxicity to the fetus and some birth defects at maternally toxic, high doses in animals. Other animal studies have not reproduced birth defects even at much higher doses that caused severe maternal toxicity.

Reproductive toxicity

Diethylene glycol did not interfere with reproduction in animal studies except at very high doses.

Mutagenicity

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Aspiration Hazard

No aspiration toxicity classification

Dimethylbis((1-oxoneodecyl)oxy)stannane

Acute oral toxicity

LD50, Rat, 892 mg/kg

Acute dermal toxicity

The dermal LD50 has not been determined.

Acute inhalation toxicity

The LC50 has not been determined.

Skin corrosion/irritation

Brief contact may cause skin irritation with local redness.

Serious eye damage/eye irritation

May cause slight temporary eye irritation.

Sensitization

Has caused allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Available data are inadequate to determine single exposure specific target organ toxicity.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

No relevant data found.

Carcinogenicity

No relevant data found.

Teratogenicity

No relevant data found.

Reproductive toxicity

No relevant data found.

Mutagenicity

Not mutagenic in Ames Test

Aspiration Hazard

No aspiration toxicity classification

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity**trans-1-Chloro-3,3,3-trifluoropropene****Acute toxicity to fish**

Material is slightly toxic to aquatic organisms on an acute basis (LC50/EC50 between 10 and 100 mg/L in the most sensitive species tested).

LC50, *Oncorhynchus mykiss* (rainbow trout), Static, 96 Hour, 38 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

EC50, *Daphnia magna*, 48 Hour, 82 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

EC50, *Pseudokirchneriella subcapitata* (green algae), 72 Hour, Growth inhibition, 106.7 mg/l

NOEC, *Pseudokirchneriella subcapitata* (green algae), 72 Hour, Growth rate, 115 mg/l

Tris(1-chloro-2-propyl) phosphate**Acute toxicity to fish**

LC50, *Pimephales promelas* (fathead minnow), 96 Hour, 51 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

EC50, *Daphnia magna* (Water flea), 48 Hour, 131 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

EC50, *Pseudokirchneriella subcapitata* (green algae), 72 Hour, 82 mg/l, OECD Test Guideline 201

NOEC, *Pseudokirchneriella subcapitata* (green algae), 72 Hour, 42 mg/l, OECD Test Guideline 201

Toxicity to bacteria

EC50, activated sludge, Respiration inhibition, 3 Hour, 784 mg/l, OECD 209 Test

Chronic toxicity to aquatic invertebrates

NOEC, *Daphnia magna* (Water flea), 21 d, 32 mg/l

Triethyl phosphate

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
LC50, Leuciscus idus (Golden orfe), static test, 48 Hour, 2,140 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, 350 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

EC50, Desmodesmus subspicatus (green algae), 72 Hour, Growth rate inhibition, 900 mg/l, OECD Test Guideline 201

Toxicity to bacteria

EC50, activated sludge, Respiration inhibition, 30 min, > 2,985 mg/l, OECD 209 Test

Polyethylene glycol

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
LC50, Pimephales promelas (fathead minnow), static test, 96 Hour, > 10,000 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

LC50, Daphnia magna (Water flea), 48 Hour, > 10,000 mg/l

Acute toxicity to algae/aquatic plants

ErC50, Skeletonema costatum (marine diatom), 72 Hour, Growth rate, > 100 mg/l

2-Ethylhexanoic acid potassium salt

Acute toxicity to fish

Information given is based on data obtained from similar substances.
LC50, Oryzias latipes (Orange-red killifish), 96 Hour, > 100 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

Information given is based on data obtained from similar substances.
EC50, Daphnia magna (Water flea), 48 Hour, 85.4 mg/l

Acute toxicity to algae/aquatic plants

Information given is based on data obtained from similar substances.
EC50, Desmodesmus subspicatus (green algae), 96 Hour, 49.3 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 21 d, 25 mg/l

Carbon dioxide

Acute toxicity to fish

May decrease pH of aquatic systems to < pH 5 which may be toxic to aquatic organisms.
LC0, Oncorhynchus mykiss (rainbow trout), 1 Hour, 240 mg/l, Method Not Specified.

Acute toxicity to aquatic invertebrates

Based on data from similar materials

NOEC, Daphnia magna (Water flea), 48 Hour, > 100 mg/l

Diethylene glycol

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
LC50, Pimephales promelas (fathead minnow), flow-through test, 96 Hour, 75,200 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 24 Hour, > 10,000 mg/l

Acute toxicity to algae/aquatic plants

Based on data from similar materials
EC50, Selenastrum capricornutum (green algae), 96 Hour, 6,500 - 13,000 mg/l

Toxicity to bacteria

EC50, activated sludge, 3 Hour, > 1,000 mg/l, OECD 209 Test

Chronic toxicity to fish

Based on data from similar materials
NOEC, Pimephales promelas (fathead minnow), 7 d, 15,380 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 21 d, > 15,000 mg/l

Dimethylbis((1-oxoneodecyl)oxy)stannane

Acute toxicity to aquatic invertebrates

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).
EC50, Daphnia magna (Water flea), 48 Hour, 39 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, 7.6 mg/l, OECD Test Guideline 201
NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, 1.2 mg/l, OECD Test Guideline 201

Toxicity to bacteria

For similar material(s):
EC50, Bacteria, 3 Hour, Respiration rates., 14 mg/l

Persistence and degradability

trans-1-Chloro-3,3,3-trifluoropropene

Biodegradability: Material is not readily biodegradable according to OECD/EEC guidelines.

Biodegradation: 0 %

Exposure time: 28 d

Method: OECD Test Guideline 301D

Tris(1-chloro-2-propyl) phosphate

Biodegradability: Not readily biodegradable.

Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301E

Theoretical Oxygen Demand: 1.17 mg/mg

Photodegradation
Test Type: Half-life (indirect photolysis)
Sensitization: OH radicals
Atmospheric half-life: 0.24 d
Method: Estimated.

Triethyl phosphate

Biodegradability: Material is ultimately biodegradable (reaches > 70% mineralization in OECD test(s) for inherent biodegradability).
10-day Window: Not applicable
Biodegradation: > 90 %
Exposure time: 28 d
Method: OECD Test Guideline 302B or Equivalent

Theoretical Oxygen Demand: 1.58 mg/mg

Polyethylene glycol

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.
10-day Window: Pass
Biodegradation: 85 %
Exposure time: 28 d
Method: OECD Test Guideline 301F or Equivalent

Theoretical Oxygen Demand: 1.67 mg/mg

2-Ethylhexanoic acid potassium salt

Biodegradability: Readily biodegradable. Information given is based on data obtained from similar substances.
Biodegradation: 99 %
Exposure time: 28 d

Carbon dioxide

Biodegradability: Biodegradation is not applicable.

Diethylene glycol

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.
10-day Window: Pass
Biodegradation: 90 - 100 %
Exposure time: 20 d
Method: OECD Test Guideline 301A or Equivalent
10-day Window: Not applicable
Biodegradation: 82 - 98 %
Exposure time: 28 d
Method: OECD Test Guideline 302C or Equivalent

Theoretical Oxygen Demand: 1.51 mg/mg

Dimethylbis((1-oxoneodecyl)oxy)stannane

Biodegradability: Material is not readily biodegradable according to OECD/EEC guidelines.

Biodegradation: 0 %

Exposure time: 28 d

Method: OECD Test Guideline 301B or Equivalent

Bioaccumulative potential

trans-1-Chloro-3,3,3-trifluoropropene

Bioaccumulation: No relevant data found.

Tris(1-chloro-2-propyl) phosphate

Bioaccumulation: Does not bioaccumulate.

Partition coefficient: n-octanol/water(log Pow): 2.68

Triethyl phosphate

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 0.80 Measured

Polyethylene glycol

Partition coefficient: n-octanol/water(log Pow): -0.698 Pow: 0.2 at 30 °C

2-Ethylhexanoic acid potassium salt

Bioaccumulation: Bioaccumulation is unlikely. Based on information for a similar material: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Carbon dioxide

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 0.83 Measured

Diethylene glycol

Bioaccumulation: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water(log Pow): -1.98 at 20 °C

Bioconcentration factor (BCF): 100 Fish Measured

Dimethylbis((1-oxoneodecyl)oxy)stannane

Partition coefficient: n-octanol/water(log Pow): 5.503

Mobility in soil

trans-1-Chloro-3,3,3-trifluoropropene

No relevant data found.

Triethyl phosphate

Potential for mobility in soil is very high (Koc between 0 and 50).

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Partition coefficient (Koc): 48 Estimated.

Polyethylene glycol

No relevant data found.

2-Ethylhexanoic acid potassium salt

Based on information for a similar material:
Potential for mobility in soil is very high (Koc between 0 and 50).

Carbon dioxide

No relevant data found.

Diethylene glycol

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.
Potential for mobility in soil is very high (Koc between 0 and 50).
Partition coefficient (Koc): < 1 Estimated.

Dimethylbis((1-oxoneodecyl)oxy)stannane

No relevant data found.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

14. TRANSPORT INFORMATION

DOT

| | |
|-----------------------------|---|
| Proper shipping name | Chemical under pressure, n.o.s.(Carbon dioxide, Nitrogen) |
| UN number | UN 3500 |
| Class | 2.2 |
| Packing group | |

Classification for SEA transport (IMO-IMDG):

| | |
|-----------------------------|---|
| Proper shipping name | CHEMICAL UNDER PRESSURE, N.O.S.(Carbon dioxide, Nitrogen) |
| UN number | UN 3500 |
| Class | 2.2 |
| Packing group | |
| Marine pollutant | No |

Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code

Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

| | |
|-----------------------------|---|
| Proper shipping name | Chemical under pressure, n.o.s.(Carbon dioxide, Nitrogen) |
| UN number | UN 3500 |
| Class | 2.2 |
| Packing group | |

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Gases under pressure
Simple Asphyxiant
Serious eye damage or eye irritation
Respiratory or skin sensitisation
Reproductive toxicity

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

This material does not contain any components with a CERCLA RQ.

Does not contain HFC.

Compliant with Title 42 Chapter 85 Clean Air Act: Subchapter VII American Innovation and Manufacturing Act of 2020, and Section 612 US EPA Significant New Alternatives Policy.

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Pennsylvania Worker and Community Right-To-Know Act:

The following chemicals are listed because of the additional requirements of Pennsylvania law:

| Components | CASRN |
|-------------------|----------|
| Diethylene glycol | 111-46-6 |
| Carbon dioxide | 124-38-9 |

California Prop. 65

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the Active inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System**HMIS**

| Health | Flammability | Physical Hazard |
|--------|--------------|-----------------|
| 2* | 1 | 3 |

* = Chronic Effects (See Hazards Identification)

Revision

Identification Number: 12075524 / A776 / Issue Date: 11/17/2024 / Version: 3.2

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

| | |
|------------|---|
| ACGIH | USA. ACGIH Threshold Limit Values (TLV) |
| AEL * | 8 & 12 hr. TWA |
| CAL PEL | California permissible exposure limits for chemical contaminants (Title 8, Article 107) |
| Dow IHG | Dow Industrial Hygiene Guideline |
| DUPONT AEL | DuPont AEL (Acceptable Exposure Limit) |
| NIOSH REL | USA. NIOSH Recommended Exposure Limits |
| OSHA Z-1 | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| PEL | Permissible exposure limit |
| ST | STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday |
| STEL | Short-term exposure limit |
| TWA | 8-hr TWA |
| US WEEL | USA. Workplace Environmental Exposure Levels (WEEL) |

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic

Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US