

SECTION 1 Identification

1.1. GHS Product identifier

Product form	: Mixture
Product name	: Synthetic Low Viscosity Multi-Vehicle ATF
Type of product	: Lubricating oil
Part Number	: 21255

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture	: Lubricating oil
Recommended use	: Automotive products
Restrictions on use	: No additional information available

1.4. Supplier's details

Lucas Oil Products, Inc.
3199 Harrison Way NW
Corydon, IN 47112
USA
T 800-342-2512
sds@lucasoil.com - www.LucasOil.com

1.5. Emergency phone number

Emergency number	: For Chemical Emergency Call ChemTel 24hr/day 7days/week Within USA, Canada, Puerto Rico and US Virgin Islands: 1-800-255-3924 International: 1-813-248-0585 (collect calls accepted)
------------------	---

SECTION 2 Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361	Suspected of damaging fertility or the unborn child.
Hazardous to the aquatic environment, Acute Hazard, Category 3	H402	Harmful to aquatic life.
Hazardous to the aquatic environment, Chronic Hazard, Category 3	H412	Harmful to aquatic life with long lasting effects.
Full text of H-statements: see section 16		

2.2. GHS label elements, including precautionary statements

GHS CA labelling

Hazard pictograms (GHS CA)	:	 
----------------------------	---	---

Signal word (GHS CA)	:	Warning
----------------------	---	---------

Hazard statements (GHS CA)	:	H317 - May cause an allergic skin reaction H361 - Suspected of damaging fertility or the unborn child
----------------------------	---	--

Synthetic Low Viscosity Multi-Vehicle ATF

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Precautionary statements (GHS CA)

H402 - Harmful to aquatic life
H412 - Harmful to aquatic life with long lasting effects
: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P261 - Avoid breathing dust, fume, gas, mist, vapours, spray.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P308+P313 - IF exposed or concerned: Get medical advice or attention.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	CAS-No.: 72623-87-1	80 - 100*	Asp. Tox. 1, H304
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	Lubricating oils (petroleum), (C=15-30), hydrotreated neutral oil-based Baseoil - unspecified / lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based / paraffin oils	CAS-No.: 72623-86-0	0.5 - 1.5*	Asp. Tox. 1, H304

Synthetic Low Viscosity Multi-Vehicle ATF

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Distillates (petroleum), hydrotreated light paraffinic	Distillates (petroleum), hydrotreated light paraffinic distillates (petroleum), hydrotreated light paraffinic	CAS-No.: 64742-55-8	0.5 - 1.5*	Asp. Tox. 1, H304
Thio alkyl long chain alkyl ester	-	CAS-No.: Undisclosed	0.012 - 0.12	Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 2, H401
4-Methyl-1H-benzotriazole	Methylbenzotriazole ; Toly triazole, Methyl-1H-benzotriazole 1H-benzotriazole, methyl- / 4-methyl-1H-benzotriazole / 5-methyl-1H-benzotriazole / COBRATEC TT-100 / COBRATEC TT-351 / methyl-1H-benzotriazole / methylbenzotriazole / OLIN 53734 / tolutriazole / tolyltriazole / TTA (=tolyltriazole) / TTZ (=tolyltriazole)	CAS-No.: 29385-43-1	0.012 - 0.12	Acute Tox. 4 (Oral), H302 Repr. 2, H361 Aquatic Chronic 2, H411

*Chemical name, CAS number and/or exact concentration have been withheld as CBI

*Contains fixed concentration

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor.
First-aid measures after skin contact	: Wash skin with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. When in doubt or if symptoms are observed, get medical advice. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Rinse mouth out with water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Call a poison center or a doctor if you feel unwell.
First-aid measures general	: If you feel unwell, seek medical advice. IF exposed or concerned: Get medical advice/attention.
Self protection of the first-aiders	: First-aiders should pay attention to their own protection and use the recommended personal protective equipment (see section 8).

Synthetic Low Viscosity Multi-Vehicle ATF

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: Redness. Itching. Skin rash/inflammation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
Symptoms/effects after ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5 Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard. In case of fire and/or explosion do not breathe fumes.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon dioxide. Carbon monoxide.

5.3. Special protective actions for fire-fighters

Firefighting instructions	: Evacuate area. Eliminate all ignition sources if safe to do so. Fight fire from safe distance and protected location. Use water spray or fog for cooling exposed containers. Prevent fire fighting water from entering the environment. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
Environmental precautions	: Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment	: Absorb spilled material with sand or earth. Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up	: Take up liquid spill into absorbent material. Move containers from fire area if it can be done without personal risk. Take up liquid spill into absorbent material. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Clean contaminated surfaces with an excess of water. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.
For further information refer to section 13.	

Synthetic Low Viscosity Multi-Vehicle ATF

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Do not breathe vapours. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Keep only in original container. Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Store locked up.
Packaging materials	: Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls	: Handle in accordance with good industrial hygiene and safety procedures. Ensure exposure is below occupational exposure limits (where available). Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves

Eye protection:

If there is a risk of liquid being splashed : Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

No respiratory protection needed under normal use conditions. In case of insufficient ventilation, wear suitable respiratory equipment. [In case of inadequate ventilation] wear respiratory protection.

Synthetic Low Viscosity Multi-Vehicle ATF

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: Mixture contains one or more component(s) which have the following colour(s): Pure substance: colourless Unpurified: light yellow White Colourless
Odour	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: Aromatic odour Characteristic odour
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: 0.84
Density	: 7.013 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 27.27 mm ² /s @ 40 ° C
Explosive limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions of use.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	: No additional information available

Synthetic Low Viscosity Multi-Vehicle ATF

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 11 Toxicological information

11.1. Likely routes of exposure

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 oral	5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
LD50 dermal	5000 mg/kg
ATE CA (oral)	5000 mg/kg bodyweight
ATE CA (Dermal)	5000 mg/kg bodyweight

Thio alkyl long chain alkyl ester (Undisclosed)

LD50 oral rat	> 10000 mg/kg
---------------	---------------

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 oral	5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
LD50 dermal	5000 mg/kg
ATE CA (oral)	5000 mg/kg bodyweight
ATE CA (Dermal)	5000 mg/kg bodyweight

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID

4-Methyl-1H-benzotriazole (29385-43-1)

LD50 oral rat	720 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
ATE CA (oral)	720 mg/kg bodyweight

Skin corrosion/irritation : Not classified

4-Methyl-1H-benzotriazole (29385-43-1)

pH	6 (0.1 %)
----	-----------

Serious eye damage/irritation : Not classified

4-Methyl-1H-benzotriazole (29385-43-1)

pH	6 (0.1 %)
----	-----------

Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Synthetic Low Viscosity Multi-Vehicle ATF

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

4-Methyl-1H-benzotriazole (29385-43-1)	
NOAEL (oral, rat, 90 days)	≈ 150 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)

Aspiration hazard : Not classified.

Synthetic Low Viscosity Multi-Vehicle ATF	
Viscosity, kinematic	27.27 mm²/s @ 40 ° C

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
Viscosity, kinematic	12 mm²/s
Hydrocarbon	Yes

4-Methyl-1H-benzotriazole (29385-43-1)	
Viscosity, kinematic	Not applicable (solid)

Symptoms/effects after inhalation : Not expected to present a significant inhalation hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : Redness. Itching. Skin rash/inflammation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Not expected to present a significant eye contact hazard under anticipated conditions of normal use.

Symptoms/effects after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

SECTION 12 Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Harmful to aquatic life.

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Synthetic Low Viscosity Multi-Vehicle ATF

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
4-Methyl-1H-benzotriazole (29385-43-1)	
LC50 - Fish [1]	55 mg/l (Equivalent or similar to OECD 203, 96 h, Cyprinodon variegatus, Semi-static system, Salt water, Experimental value)
EC50 - Other aquatic organisms [1]	15.8 mg/l Test organisms (species): other aquatic crustacea:
EC50 - Other aquatic organisms [2]	8.58 mg/l Test organisms (species): other aquatic crustacea:
EC50 72h - Algae [1]	53 mg/l (ISO 10253, Skeletonema costatum, Static system, Salt water, Experimental value, Growth rate)
EC50 96h - Algae [1]	13.795 mg/l Source: ECOSAR
NOEC (chronic)	18.4 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
LOEC (chronic)	37.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

Synthetic Low Viscosity Multi-Vehicle ATF	
Persistence and degradability	Biodegradability in water: no data available.
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
Persistence and degradability	Not rapidly degradable
Thio alkyl long chain alkyl ester (Undisclosed)	
Persistence and degradability	Not rapidly degradable
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
Persistence and degradability	Not rapidly degradable
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
Persistence and degradability	Not rapidly degradable
4-Methyl-1H-benzotriazole (29385-43-1)	
Persistence and degradability	Not readily biodegradable in water.
Biochemical oxygen demand (BOD)	0 g O ₂ /g substance
Chemical oxygen demand (COD)	1.83 g O ₂ /g substance

Synthetic Low Viscosity Multi-Vehicle ATF

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

12.3. Bioaccumulative potential

Synthetic Low Viscosity Multi-Vehicle ATF

Bioaccumulative potential	No data available concerning bioaccumulation.
---------------------------	---

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
---	------------------------

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
---	------------------------

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
---	------------------------

4-Methyl-1H-benzotriazole (29385-43-1)

Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
---------------------------	--

BCF - Fish [1]	2.4 l/kg (BCFBAF v3.00)
----------------	-------------------------

BCF - Other aquatic organisms [1]	4.168 (BCFWIN, Calculated value)
-----------------------------------	----------------------------------

Partition coefficient n-octanol/water (Log Pow)	1.079 – 1.083 (Practical experience/observation, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
---	---

12.4. Mobility in soil

Synthetic Low Viscosity Multi-Vehicle ATF

Ecology - soil	No additional information available.
----------------	--------------------------------------

4-Methyl-1H-benzotriazole (29385-43-1)

Ecology - soil	No (test)data on mobility of the substance available.
----------------	---

12.5. Other adverse effects

Ozone : Not classified

Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.
Ecological waste information	: The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

SECTION 14 Transport information

In accordance with TDG / DOT / IMDG / IATA

Synthetic Low Viscosity Multi-Vehicle ATF

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

TDG	DOT	IMDG	IATA
14.1. UN Number			
Not regulated for transport			
14.2. UN Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group, if applicable			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Special precautions for user

TDG

Not regulated

DOT

Not regulated

IMDG

Not regulated

IATA

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78⁹ and the IBC Code¹⁰

Not applicable

SECTION 15 Regulatory information

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

Listed on the Canadian DSL (Domestic Substances List)

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

Listed on the Canadian DSL (Domestic Substances List)

4-Methyl-1H-benzotriazole (29385-43-1)

Listed on the Canadian DSL (Domestic Substances List)

Synthetic Low Viscosity Multi-Vehicle ATF

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Synthetic Low Viscosity Multi-Vehicle ATF

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Thio alkyl long chain alkyl ester (Undisclosed)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

4-Methyl-1H-benzotriazole (29385-43-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

SECTION 16 Other Information

Issue date : 04/29/2025
Revision date : 03/26/2026
Supersedes : 09/04/2025

Training advice : Training staff on good practice.

Full text of hazard classes and H-statements:

H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H361	Suspected of damaging fertility or the unborn child
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Abbreviations and acronyms:

ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

Synthetic Low Viscosity Multi-Vehicle ATF

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Abbreviations and acronyms:	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAS-No.	Chemical Abstracts Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
CSA	Chemical safety assessment
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
ED	Endocrine disruptor
EN	European Standard
EWC	European waste catalogue
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
Log Kow	Partition coefficient n-octanol/water (Log Kow)
Log Pow	Partition coefficient n-octanol/water (Log Pow)
MAK	maximum workplace concentration
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
N.O.S.	Not Otherwise Specified
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
OSHA	Occupational Safety & Health Administration
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
PPE	Personal protection equipment
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail

Synthetic Low Viscosity Multi-Vehicle ATF

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Abbreviations and acronyms:

SDS	Safety Data Sheet
STP	Sewage treatment plant
TF	Technical function
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
TWA	Time Weighted Average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative
UFI	Unique Formula Identifier

Safety Data Sheet (SDS), Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.